





MAT FROST STATIC

Mat Frosted Static privacy films are designed to provide protection against the scrutiny of prying eyes. Whilst completely opalescent, the film still allows most natural light to pass through. With disposable plastic liner or silicone paper liner for digital cutting. In addition, this "static" version is easy ton install.



Storage from -5°C to +40°C
3 YEARS



REACH RoHS compliant
RESPECTED

WIDTHS AVAILABLE:

↔ **152 cm**

TECHNICAL DATASHEET

Data calculated based on film applied to clear glass 3 mm thick (*on double glazing 4-16-4)

Ultraviolet transmission	>25 %
Visible light transmission	76 %
Reflection of external visible light	15 %
Reflection of internal visible light	15 %
Total solar energy rejected	18 %
Total solar energy rejected 2*	19 %
Solar ratio :	
Solar energy reflection	10 %
Solar energy absorption	17 %
Solar energy transmission	73 %
Reduction in Solar Glare	20 %
g-value	0,77
u-value	5,6
Shading coefficient	NC
Installation type : Interior	
Roll length	20 m
Film composition	PVC
Thickness	100 μ
Colour from the outsideFROSTED	

INSTALLATION ADVICE

Vertical installation and on standard glass surface**


Clear single pane	✓
Tinted single pane	✓
Reflective tinted single pane	✓
Clear double pane	✓
Tinted double pane	✓
Reflective tinted double pane	✓
Gas-filled double pane - Low E	✓
STADIP EXT. clear double pane	✓
STADIP INT. clear double pane	✓

✓ Yes ⚠ Caution ✗ Not recommended

*Recommendations provided on the basis of a glazed surface covering up to 2.5m².

CONSTRUCTION

1. 100μ Frosted monomer PVC
2. Protection liner, disposable after the installation



MAINTENANCE INSTRUCTIONS

Soapy water solution (ref. 0805 Film on), do not clean for at least a month and do not apply any type of sticker or adhesive on the film.