

NETWORK CONNECTED POS SCREEN
DIAGONAL 15.6"
P16KDTAB02NS

**PRODUCT SPECIFICATION**

CPU	Rockchip RK3288, quad-core Cortex-A17, GPU Mail-T764
Frequency	2.2 GHz
RAM	DDR3 2G default/4G (upgradable)
Internal Storage	EMMC 8GB default/16G or 32G (upgradable), supports NAND FLASH.
Resolution/Aspect Ratio	1920x1080/16:9
Viewing Angle	89/89/89/89
Network Support	With RJ45 port, supports 10/100/1000M Ethernet. Built-in Wifi & BT module, supports Wi-Fi 802.11b/g/n (ac upgradable), BT4.0.
Clock	Built-in battery power supply.
User Interface	USB 2.0 Host x2 TF card, supports up to 32GB HDMI 2.0 input.
Hardware Keys	7 Buttons (Menu /Esc/Vol-/Vol+/Next/Prev/Enter)
Stereo Speaker	3Wx2
Brightness	300nits
Contrast	1000:1
Lifetime	20000hrs
Audio	MP3,WMA,WAV, APE, FLAC, AAC, OGG,M4A,3GPP
Video	H.264, MPEG2, VP6, VP8 ,MVC 2160P@24FPS. YouTube online video play, up to 1080P, HTML5, Flash10.1.
Picture	Supports PNG,BMP,JPG
Power Adapter	Input: AC100-240V.50-60HZ Output: DC12V 3A.
Operation System	Google Android 6.0
Language	Multiple languages.
	Supports OTA remote upgrade, disk upgrade

NETWORK CONNECTED POS SCREEN
DIAGONAL 15.6"
P16KDTAB02NS

System Management	Open root privileges
	Customizable local or remote server management system.
	Supports multiple serial devices, USB devices, IO control devices
Wall mount	VESA 75mm
Weight	2.2Kg
Operation Condition	0°C~40°C
Storage Condition	-20°C~55°C

Dimension: