

**NETWORK CONNECTED POS SCREEN**  
**DIAGONAL 21.5"**  
P215KDTAB02NS

**PRODUCT SPECIFICATION**

|                         |  |
|-------------------------|--|
| CPU                     | Rockchip RK3288, quad-core Cortex-A17, GPU Mail-T764   |
| Frequency               | 2.2 GHz  |
| RAM                     | DDR3 2G default/4G (upgradable)  |
| Internal Storage        | EMMC 8GB default/16G or 32G (upgradable), supports NAND FLASH.   |
| Resoluton/ Aspect Ratio | 1920x1080/16:9   |
| Viewing Angle           | 89/89/89/89  |
| Network Support         | With RJ45 port, supports 10/100/1000M Ethernet.<br>Built-in Wifi & BT module, supports Wi-Fi 802.11b/g/n (ac upgradable), BT4.0. |
| Clock                   | Built-in battery power supply.   |
| User Interface          | USB 2.0Host x2<br>TF card, supports up to 32GB<br>HDMI 2.0 input.  |
| Hardware Keys           | 5 Buttons ( Menu /Vol-/Vol+/Prev/Enter)+Power switch   |
| Stereo Speaker          | 3Wx2   |
| Brightness              | 250nits  |
| Contrast                | 1000:1   |
| Lifetme                 | 30000hrs   |
| Audio                   | MP3,WMA,WAV, APE, FLAC, AAC, OGG,M4A,3GPP  |
| Video                   | H.264, MPEG2, VP6, VP8, MVC 2160P@24FPS.<br>YouTube online video play, up to 1080P, HTML5, Flash10.1.                            |
| Picture                 | Supports PNG,BMP,JPG   |
| Power Adapter           | Input: AC100-240V.50-60HZ Output: DC12V 3A.  |
| Operation S stem        | Google Android 6.0   |
| Language                | Multiple languages.  |
|                         | Supports OTA remote upgrade, disk upgrade  |

**NETWORK CONNECTED POS SCREEN**  
**DIAGONAL 21.5"**  
P215KDTAB02NS

|                   |   |
|-------------------|---|
| System Management | Open root privileges  |
|                   | Customizable local or remote server management system.            |
|                   | Supports multiple serial devices, USB devices, IO control devices |
| Wall mount        | VESA 100mm  |
| Weight            | 3.5Kg   |
| Operaton Connditn | 0°C~40°C  |
| Storage Condition | -20°C~55°C  |

**Dimension:**