

**NETWORK CONNECTED POS SCREEN  
DIAGONAL 27"  
P27KDTAB02NS**

**Product Specification**

CPU	Rockchip RK3288, quad-core Cortex-A17, GPU Mail-T764
Frequency	2.2 GHz
RAM	DDR3 2G default/4G (upgradable)
Internal Storage	EMMC 8GB default/16G or 32G (upgradable), supports NAND FLASH.
Resoluton/Aspect Ratio	1920x1080/16:9
Viewing Angle	89/89/89/89
Network Support	With RJ45 port, supports 10/100/1000M Ethernet. Built-in Wifi & BT module, supports Wi-Fi 802.11b/g/n (ac upgradable), BT4.0.
Clock	Built-in battery power supply.
User Interface	USB 2.0Host x2 TF card, supports up to 32GB HDMI 2.0 input.
Hardware Keys	5 Buttons ( M nu /Vol-/Vol+/Prev/Enter)+Power switch
Stereo Speaker	5Wx2
Brightness	300 nits
Contrast	1000:1
Lifetme	30000 hrs
Audio	MP3,WMA,WAV, APE, FLAC, AAC, OGG,M4A,3GPP
Video	H.264, MPEG2, VP6, VP8, MVC 2160P@24FPS. YouTube online video play, up to 1080P, HTML5
Picture	Supports PNG,BMP,JPG
Power Adapter	Input: AC100-240V.50-60HZ Output: DC12V 5A.
Operation S stem	Google Android 6.0
Language	Multpl e languages.
	Supports OTA remote upgrade, disk upgrade

**NETWORK CONNECTED POS SCREEN**  
**DIAGONAL 27"**  
P27KDTAB02NS

System Management	Open root privileges
	Customizable local or remote server management system.
	Supports multiple serial devices, USB devices, IO control devices
Wall mount	VESA 100mm
Weight	4.85Kg
Operation Condition	0°C~40°C
Storage Condition	-20°C~55°C

**Dimension:**