

P55KDTAB02NS

55" android display



Product Specification

CPU	Rockchip RK3288, quad-core Cortex-A17, GPU Mail-T764
Frequency	2.2 GHz
RAM	DDR3 2G default/4G (upgradable)
Resolution/Aspect Ratio	1920x1080/16:9
Viewing Angle	89/89/89/89
Internal Storage	EMMC 8GB default/16G or 32G (upgradable), supports NAND FLASH.
Network Support	With RJ45 port, supports 10/100/1000M Ethernet.
	Built-in Wifi & BT module, supports Wi-Fi 802.11b/g/n (ac upgradable), BT4.0.
Clock	Built-in battery power supply.
User Interface	USB 2.0 Host x2
	TF card, supports up to 32GB
Hardware Keys	7 Buttons (Menu /Esc/Vol-/Vol+/Next/Prev/Enter)
Stereo Speaker	10Wx2
Brightness	300nits
Contrast	1200:1
Lifetime	30000 hrs
Audio	MP3,WMA,WAV, APE, FLAC, AAC, OGG,M4A,3GPP
Video	H.264, MPEG2, VP6, VP8, MVC 2160P@24FPS.
	YouTube online video play, up to 1080P, HTML5, Flash10.1.
Picture	Supports PNG,BMP,JPG
Power Adapter	Input: AC100-240V.50-60HZ
Operation System	Google Android 6.0
Language	Multiple languages.
System Management	Supports OTA remote upgrade, disk upgrade
	Open root privileges

	Customizable local or remote server management system.
	Supports multiple serial devices, USB devices, IO control devices
Wall mount	VESA 400mm
Weight	9.2Kg
Operation Condition	0°C~40°C
Storage Condition	-20°C~55°C

Dimension:

